



CEILING HUNG

Uranus series offers unobstructed floor space for ease of housekeeping and maintenance. Structural steel support in the ceiling is required. This system is best suited for ceiling heights 2440mm or less and is not recommended above that height.



Unobstructed clearance below cubicle are meant for easy cleaning and maintenance

URANUS

Exceeding
Your Expectations
of Value

SPECIFICATION

General

Toilet cubicle system shall be '**PRO-CUBIX' Uranus Series** ceiling hung toilet cubicle system; manufactured by **Procubix Contracts Sdn Bhd**.

Panels

Shall be 12mm thick solid compact laminates made from impregnated kraft paper with phenolic resin, compressed together with melamine impregnated decorative paper under high pressure temperature to form high pressure laminates. Two-piece construction is not acceptable.

Panels shall be the following characteristics: humidity resistant, scratch and wear resistant, easy to clean.

Doors

Shall be of the same materials an construction as panels. Thickness shall be of either 12mm or 18mm thickness. Door size shall 1800mm height and of width to suit site condition. It shall be rebated at 2 vertical end.

Pilasters

Shall be the same materials as panels and doors. Thickness shall be 12mm or 18mm thickness. Pilasters shall be also rebated to suit door panels. Pilasters shall be fastened on top; to structural galvanized iron support above ceiling with nuts and bolts and to wall by means stainless steel angle brackets.

Hardware

Nylon (Option 1)

Comprises of nylon thumb-turn indicator bolt, gravity hinges and coat hook.

Stainless Steel (Option 2)

Comprises of stainless steel indicator bolt, coat hook with rubber bumper and heavy-duty gravity hinges.

Fittings

Angle brackets comprises of two holes for fastening purpose. All hardware and fittings shall be fastened with one-way fasteners for vandalism prevention.

Colours

Panel colours shall be in accordance to manufacturer's colours swatch.

All extruded aluminium fittings shall in natural anodized or powder-coated black colour to match.

Stainless steel hardware shall be in satin finish.

Nylon hardware shall be in standard black color or other color available upon request.

Dimensions

Overall system height : 2400mm height with 150mm floor clearance, or to suit site conditions.



Lock set (outside view)



Thumb-turn lock set (outside view)



Lock set (inside view)



Thumb-turn lock set (inside view)



Coat hook with rubber bumper



Coat hook



Gravity hinge



Gravity hinge



1/2" bracket



1/2" bracket

Manufacturer & Fabricator:



PROCUBIX CONTRACTS SDN BHD

Wisma APIC, No. 28 & 30, Jalan Beliong 15/11, Seksyen 15, 40200 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel : (603) 5519 6127

Fax : (603) 5512 7950

E-mail : gen@tsigm.com

Website : <http://www.procubix.com>



Exceeding
Your Expectations
of Value