



FLOOR MOUNTED

Ideal for restrooms that have high ceiling space. Flush top line gives a modern appearance while simplified construction allows for easy installation. The uniform overall height of pilaster and door creates a pleasing visual appearance. It is also adaptable to any style building and interior requirement.



Frameless system that uses only stainless steel bracket thus creating a cleaner & neater appearance.



Doors and pilasters are rebatted to perform an overlapped effect without door jamb.

VENUS

Exceeding
Your Expectations
of Value

SPECIFICATION

General

Toilet cubicle system shall be **'Pro-CUBIX' Venus Series** floor-mounted toilet cubicle system; manufactured by **APIC Sdn Bhd.**

Panels

Shall be of either 13mm or 15mm thickness solid compact laminates made from impregnated kraft paper with phenolic resin, compressed together with melamine impregnated decorative paper under high pressure temperature to form high pressure laminates. Two-piece construction is not acceptable.

Panels shall have following characteristic: humidity resistant, scratch resistant, easy to clean.

Doors

Shall be of the same materials and construction as panels. Thickness shall be of either 19mm or 22mm thickness. Door size shall 1680mm height and of width to suit site condition. It shall be rebated at 2 vertical end.

Pilasters

Shall be of the same material as panels and doors. Thickness shall be of 19mm or 22mm thickness. Pilaster shall be also rebated to suit the door panels.

Pilasters shall be fastened to a full length steel bar by means of two bolts into cross dowels and to the floor with two nos threaded rods with nuts and lock washers and lead double expansion shields. Floor anchoring shall be concealed by a 100mm high one-piece stainless steel floor shoe.

Hardware

Comprises of stainless steel slide indicator latch, coat hook with rubber bumper and heavy duty gravity hinges.

Fittings

Angle brackets shall be of minimum 1.8m thickness stainless steel with two holes for fastening purpose.

Stainless steel floor shoe shall be of one-piece construction in 0.9mm thickness minimum.

All hardware and fittings shall be fastened with one-way fasteners for vandalism prevention.

Colours

Panel colour shall be in accordance to manufacturer's colour swatch. Hardware and fittings shall be in stainless steel satin finish.

Dimensions

Overall system height: 1800mm height with 120mm floor clearance



Coat hook with rubber bumper



Lock set (outside view)



Lock set (inside view)



Gravity hinge



"L" bracket



Shoe Trim

Manufacturer & Fabricator:



PROCUBIX CONTRACTS SDN BHD

(487651-X)

Wisma APIC, No. 28 & 30, Jalan Beliong 15/11,
Seksyen 15, 40200 Shah Alam,
Selangor Darul Ehsan, Malaysia.

Tel: +603 5519 6127 Fax: +603 5512 7950

Email: gen@tsigm.com

http://www.tsigm.com http://www.procubix.com



Exceeding
Your Expectations
of Value